

SLV-Series Sleeve Valve


SLV-Series sleeve valves combines high flow capability with short stroke in a small package. Unlike ball valves, sleeve valves do not require space for a handle.

SLV-Series sleeve valves features smooth opening/closing operation. Outlet is exhausted to atmosphere when the valves is closed.

Unit is constructed of brass body and anodized aluminum sleeve for corrosion resistance.



SYMBOL



HOW TO ORDER

SLV

Sleeve Valve

—



—



Connection (NPT)

18 = 1/8", 28 = 1/4"

38 = 3/8", 48 = 1/2"

Port Option

None = Female Inlet

M = Male Inlet



California Proposition 65 Warning

WARNING: This product can expose you to chemicals, including lead, which is known to the state of California to cause Cancer, Birth Defects or other reproductive harm. For more information go to www.p65warnings.ca.gov

SPECIFICATIONS

ITEM	MODEL	SLV-18	SLV-28	SLV-38	SLV-48
CONNECTION	NPT	1/8"-27 M-F	1/4"-18 M-F	3/8"-18 M-F	1/2"-14 M-F
FLUID	AIR ONLY				
VALVE FUNCTION	2-POSITION, 3-WAY, VENT TO EXHAUST				
LENGTH	IN. (mm)	2-11/16" (68.0)	2-27/32" (72.0)	3" (76.0)	3-5/8" (92.0)
HEX	IN. (mm)	5/8" (16.0)	43/64" (17.0)	3/4" (19.0)	61/64" (24.0)
SLEEVE DIAMETER	IN. (mm)	1-13/16" (30.0)	1-13/16" (30.0)	1-13/16" (30.0)	1-7/8" (47.5)
MATERIAL	BODY	BRASS			
	SLEEVE	ANODIZED ALUMINUM			
OPERATING PRESSURE	0 ~ 140 PSI (0 ~ 10 kg/cm ²)				
OPERATING TEMPERATURE	41° ~ 140° F (5° ~ 60°C)				
WEIGHT	OZ.	3.30	3.38	3.69	9.06