





### ■ DIMENSIONS

CS-71D, CS-71N, CS-71P / CS-71D-QD, CS-71N-QD, CS-71P-QD




### ■ SW OUT




### ■ QD PINOUT


\*3 wire QD wiring



\*2 wire QD wiring



\*2 wire EQD wiring



### ■ SPECIFICATIONS

TYPE	CS-71D	CS-71N	CS-71P
CONNECT DIAGRAM			
CHARACTERISTICS			
Wiring Method	2-Wire Type	3-Wire Type	
Switching Logic	Solid State Output, Normally Open		
Sensor Type	-	NPN Current Sinking	PNP Current Sourcing
Operating Voltage	10~28V DC		
Switching Current	80mA max.		
Contact Rating (*1)	2W max.		
Current Consumption	-	10mA @ 24V DC max.	
Voltage Drop	4V max.	1.5V max.	
Leakage Current	1mA max.	0.05mA max.	
Indicator	Red / Green LED		
Cable	ø2.8, 2C, PUR	ø2.8, 3C, PUR	
Operating Frequency	1000Hz		
Magnet Requirement (*2)	85Gauss		
Temperature Range	-10~60°C (+14~140°F)		
Shock (*3)	50G		
Vibration (*4)	9G		
Enclosure Classification	IEC 60529 IP67 (NEMA 6)		
Protection Circuit (*5)	2,3,4		

- NOTE:
1. WARNING: Never exceed rating (Watt=Voltage x Amperage). Permanent damage to sensor will occur.
  2. Measuring standard target: ø15.5Xø8X5t (Anisotropy rubber magnet)
  3. Sin wave / X, Y, Z 3 directions / 3 times each direction / 11 ms each time.
  4. Double amplitude 1.5 mm / 10Hz~55Hz~10Hz (Sweep 1 min) / X, Y, Z 3 directions / 1 hour each time.
  5. 1=None / 2=Short-circuit / 3=Power Source Reverse polarity / 4=Surge Suppression

### ■ GROOVE DIMENSIONS

